
Page 17





- Runoff

Appendix B



Massachusetts Department of Environmental Protection

Bureau of Resource Protection - Wetlands Program

Checklist for Stormwater Report

A. Introduction

Important: When filling out forms on the computer, use only the tab key to move your cursor - do not use the return key.





A Stormwater Report must be submitted with the Notice of Intent permit application to document compliance with the Stormwater Management Standards. The following checklist is NOT a substitute for the Stormwater Report (which should provide more substantive and detailed information) but is offered here as a tool to help the applicant organize their Stormwater Management documentation for their Report and for the reviewer to assess this information in a consistent format. As noted in the Checklist, the Stormwater Report must contain the engineering computations and supporting information set forth in Volume 3 of the Massachusetts Stormwater Handbook. The Stormwater Report must be prepared and certified by a Registered Professional Engineer (RPE) licensed in the Commonwealth.

The Stormwater Report must include:

- The Stormwater Checklist completed and stamped by a Registered Professional Engineer (see page 2) that certifies that the Stormwater Report contains all required submittals. This Checklist is to be used as the cover for the completed Stormwater Report.
- Applicant/Project Name
- Project Address
- Name of Firm and Registered Professional Engineer that prepared the Report
- Long-Term Pollution Prevention Plan required by Standards 4-6
- Construction Period Pollution Prevention and Erosion and Sedimentation Control Plan required by Standard 8²
- Operation and Maintenance Plan required by Standard 9

In addition to all plans and supporting information, the Stormwater Report must include a brief narrative describing stormwater management practices, including environmentally sensitive site design and LID techniques, along with a diagram depicting runoff through the proposed BMP treatment train. Plans are required to show existing and proposed conditions, identify all wetland resource areas, NRCS soil types, critical areas, Land Uses with Higher Potential Pollutant Loads (LUHPPL), and any areas on the site where infiltration rate is greater than 2.4 inches per hour. The Plans shall identify the drainage areas for both existing and proposed conditions at a scale that enables verification of supporting calculations.

As noted in the Checklist, the Stormwater Management Report shall document compliance with each of the Stormwater Management Standards as provided in the Massachusetts Stormwater Handbook. The soils evaluation and calculations shall be done using the methodologies set forth in Volume 3 of the Massachusetts Stormwater Handbook.

To ensure that the Stormwater Report is complete, applicants are required to fill in the Stormwater Report Checklist by checking the box to indicate that the specified information has been included in the Stormwater Report. If any of the information specified in the checklist has not been submitted, the applicant must provide an explanation. The completed Stormwater Report Checklist and Certification must be submitted with the Stormwater Report.

¹ The Stormwater Report may also include the Illicit Discharge Compliance Statement required by Standard 10. If not included in the Stormwater Report, the Illicit Discharge Compliance Statement must be submitted prior to the discharge of stormwater runoff to the post-construction best management practices.

² For some complex projects, it may not be possible to include the Construction Period Erosion and Sedimentation Control Plan in the Stormwater Report. In that event, the issuing authority has the discretion to issue an Order of Conditions that approves the project and includes a condition requiring the proponent to submit the Construction Period Erosion and Sedimentation Control Plan before commencing any land disturbance activity on the site.



Massachusetts Department of Environmental Protection

Bureau of Resource Protection - Wetlands Program

Checklist for Stormwater Report

B. Stormwater Checklist and Certification

The following checklist is intended to serve as a guide for applicants as to the elements that ordinarily need to be addressed in a complete Stormwater Report. The checklist is also intended to provide conservation commissions and other reviewing authorities with a summary of the components necessary for a comprehensive Stormwater Report that addresses the ten Stormwater Standards.


Note: Because stormwater requirements vary from project to project, it is possible that a complete Stormwater Report may not include information on some of the subjects specified in the Checklist. If it is determined that a specific item does not apply to the project under review, please note that the item is not applicable (N.A.) and provide the reasons for that determination.

A complete checklist must include the Certification set forth below signed by the Registered Professional Engineer who prepared the Stormwater Report.

Registered Professional Engineer's Certification

I have reviewed the Stormwater Report, including the soil evaluation, computations, Long-term Pollution Prevention Plan, the Construction Period Erosion and Sedimentation Control Plan (if included), the Long-term Post-Construction Operation and Maintenance Plan, the Illicit Discharge Compliance Statement (if included) and the plans showing the stormwater management system, and have determined that they have been prepared in accordance with the requirements of the Stormwater Management Standards as further elaborated by the Massachusetts Stormwater Handbook. I have also determined that the information presented in the Stormwater Checklist is accurate and that the information presented in the Stormwater Report accurately reflects conditions at the site as of the date of this permit application.

Registered Professional Engineer Block and Signature





Checklist

	ject Type: Is the application for new development, redevelopment, or a mix of new and evelopment?
\boxtimes	New development
	Redevelopment
	Mix of New Development and Redevelopment



Massachusetts Department of Environmental Protection

Bureau of Resource Protection - Wetlands Program

Checklist for Stormwater Report

Ch	ecklist (continued)	
envi	Measures: Stormwater Standards require LID measures to be considered. Document what ironmentally sensitive design and LID Techniques were considered during the planning and desproject:	sign of
\boxtimes	No disturbance to any Wetland Resource Areas	
	Site Design Practices (e.g. clustered development, reduced frontage setbacks)	
	Reduced Impervious Area (Redevelopment Only)	
\boxtimes	Minimizing disturbance to existing trees and shrubs	
	LID Site Design Credit Requested:	
	Credit 1	
	☐ Credit 2	
ļ	Credit 3	
	Use of "country drainage" versus curb and gutter conveyance and pipe	
	Bioretention Cells (includes Rain Gardens)	
	Constructed Stormwater Wetlands (includes Gravel Wetlands designs)	
	Treebox Filter	
	Water Quality Swale	
	Grass Channel	
	Green Roof	
	Other (describe):	
Star	ndard 1: No New Untreated Discharges	
	No new untreated discharges	
	Outlets have been designed so there is no erosion or scour to wetlands and waters of the	

☐ Supporting calculations specified in Volume 3 of the Massachusetts Stormwater Handbook included.

Commonwealth



Cr	necklist (contin	ued)				
Sta	ndard 2: Peak Rat	e Attenuation				
	 Standard 2 waiver requested because the project is located in land subject to coastal storm flowage and stormwater discharge is to a wetland subject to coastal flooding. Evaluation provided to determine whether off-site flooding increases during the 100-year 24-hour storm. 					
	Calculations provided to show that post-development peak discharge rates do not exceed pre- development rates for the 2-year and 10-year 24-hour storms. If evaluation shows that off-site flooding increases during the 100-year 24-hour storm, calculations are also provided to show that post-development peak discharge rates do not exceed pre-development rates for the 100-year 24- hour storm.					
Sta	ndard 3: Recharge	,				
	Soil Analysis provid	ded.				
\boxtimes	Required Recharge Volume calculation provided.					
	Required Recharge volume reduced through use of the LID site Design Credits.					
	Sizing the infiltration, BMPs is based on the following method: Check the method used.					
	Static	Simple Dynamic	☐ Dynamic Field ¹			
	Runoff from all impe	ervious areas at the site dischar	ging to the infiltration BMP.			
\boxtimes	Runoff from all impervious areas at the site is <i>not</i> discharging to the infiltration BMP and calculations are provided showing that the drainage area contributing runoff to the infiltration BMPs is sufficient to generate the required recharge volume.					
\boxtimes	Recharge BMPs ha	ave been sized to infiltrate the Re	equired Recharge Volume.			
	Recharge BMPs have been sized to infiltrate the Required Recharge Volume <i>only</i> to the maximum extent practicable for the following reason:					
	Site is comprised solely of C and D soils and/or bedrock at the land surface					
	M.G.L. c. 21E sites pursuant to 310 CMR 40.0000					
	Solid Waste La	andfill pursuant to 310 CMR 19.0	00			
	Project is other practicable.	wise subject to Stormwater Man	agement Standards only to the maximum extent			
\boxtimes	Calculations showing	ng that the infiltration BMPs will o	drain in 72 hours are provided.			
	Property includes a	M.G.L. c. 21E site or a solid wa	ste landfill and a mounding analysis is included.			

¹ 80% TSS removal is required prior to discharge to infiltration BMP if Dynamic Field method is used.



Cł	necklist (continued)
Sta	ndard 3: Recharge (continued)
	The infiltration BMP is used to attenuate peak flows during storms greater than or equal to the 10-year 24-hour storm and separation to seasonal high groundwater is less than 4 feet and a mounding analysis is provided.
	Documentation is provided showing that infiltration BMPs do not adversely impact nearby wetland resource areas.
Sta	ndard 4: Water Quality
The	E Long-Term Pollution Prevention Plan typically includes the following: Good housekeeping practices; Provisions for storing materials and waste products inside or under cover; Vehicle washing controls; Requirements for routine inspections and maintenance of stormwater BMPs; Spill prevention and response plans; Provisions for maintenance of lawns, gardens, and other landscaped areas; Requirements for storage and use of fertilizers, herbicides, and pesticides; Pet waste management provisions; Provisions for operation and management of septic systems; Provisions for solid waste management; Snow disposal and plowing plans relative to Wetland Resource Areas; Winter Road Salt and/or Sand Use and Storage restrictions; Street sweeping schedules; Provisions for prevention of illicit discharges to the stormwater management system; Documentation that Stormwater BMPs are designed to provide for shutdown and containment in the event of a spill or discharges to or near critical areas or from LUHPPL; Training for staff or personnel involved with implementing Long-Term Pollution Prevention Plan; List of Emergency contacts for implementing Long-Term Pollution Prevention Plan.
	A Long-Term Pollution Prevention Plan is attached to Stormwater Report and is included as an attachment to the Wetlands Notice of Intent. Treatment BMPs subject to the 44% TSS removal pretreatment requirement and the one inch rule for calculating the water quality volume are included, and discharge: is within the Zone II or Interim Wellhead Protection Area is near or to other critical areas is within soils with a rapid infiltration rate (greater than 2.4 inches per hour)
	involves runoff from land uses with higher potential pollutant loads.
	The Required Water Quality Volume is reduced through use of the LID site Design Credits.
Ц	Calculations documenting that the treatment train meets the 80% TSS removal requirement and, if applicable, the 44% TSS removal pretreatment requirement, are provided.



Cr	necklist (continued)					
Sta	ndard 4: Water Quality (continued)					
\boxtimes	□ The BMP is sized (and calculations provided) based on:					
	☐ The ½" or 1" Water Quality Volume or					
	☐ The equivalent flow rate associated with the Water Quality Volume and documentation is provided showing that the BMP treats the required water quality volume.					
	The applicant proposes to use proprietary BMPs, and documentation supporting use of proprietary BMP and proposed TSS removal rate is provided. This documentation may be in the form of the propriety BMP checklist found in Volume 2, Chapter 4 of the Massachusetts Stormwater Handbook and submitting copies of the TARP Report, STEP Report, and/or other third party studies verifying performance of the proprietary BMPs.					
	A TMDL exists that indicates a need to reduce pollutants other than TSS and documentation showing that the BMPs selected are consistent with the TMDL is provided.					
Sta	ndard 5: Land Uses With Higher Potential Pollutant Loads (LUHPPLs)					
	The NPDES Multi-Sector General Permit covers the land use and the Stormwater Pollution Prevention Plan (SWPPP) has been included with the Stormwater Report. The NPDES Multi-Sector General Permit covers the land use and the SWPPP will be submitted <i>prio</i> to the discharge of stormwater to the post-construction stormwater BMPs.					
\boxtimes	The NPDES Multi-Sector General Permit does <i>not</i> cover the land use.					
	LUHPPLs are located at the site and industry specific source control and pollution prevention measures have been proposed to reduce or eliminate the exposure of LUHPPLs to rain, snow, snow melt and runoff, and been included in the long term Pollution Prevention Plan.					
	All exposure has been eliminated.					
	All exposure has <i>not</i> been eliminated and all BMPs selected are on MassDEP LUHPPL list.					
	The LUHPPL has the potential to generate runoff with moderate to higher concentrations of oil and grease (e.g. all parking lots with >1000 vehicle trips per day) and the treatment train includes an oil grit separator, a filtering bioretention area, a sand filter or equivalent.					
Sta	ndard 6: Critical Areas					
\boxtimes	The discharge is near or to a critical area and the treatment train includes only BMPs that MassDEP has approved for stormwater discharges to or near that particular class of critical area.					
	Critical areas and BMPs are identified in the Stormwater Report.					



Ch	necklist (continued)
	ndard 7: Redevelopments and Other Projects Subject to the Standards only to the maximum ent practicable The project is subject to the Stormwater Management Standards only to the maximum Extent Practicable as a:
	☐ Limited Project
	 Small Residential Projects: 5-9 single family houses or 5-9 units in a multi-family development provided there is no discharge that may potentially affect a critical area. Small Residential Projects: 2-4 single family houses or 2-4 units in a multi-family development with a discharge to a critical area Marina and/or boatyard provided the hull painting, service and maintenance areas are protected from exposure to rain, snow, snow melt and runoff
	☐ Bike Path and/or Foot Path
	Redevelopment Project
	Redevelopment portion of mix of new and redevelopment.
	Certain standards are not fully met (Standard No. 1, 8, 9, and 10 must always be fully met) and an explanation of why these standards are not met is contained in the Stormwater Report. The project involves redevelopment and a description of all measures that have been taken to improve existing conditions is provided in the Stormwater Report. The redevelopment checklist found in Volume 2 Chapter 3 of the Massachusetts Stormwater Handbook may be used to document that the proposed stormwater management system (a) complies with Standards 2, 3 and the pretreatment and structural BMP requirements of Standards 4-6 to the maximum extent practicable and (b) improves existing conditions.
Sta	ndard 8: Construction Period Pollution Prevention and Erosion and Sedimentation Control
	Construction Period Pollution Prevention and Erosion and Sedimentation Control Plan must include the owing information:
	 Narrative; Construction Period Operation and Maintenance Plan; Names of Persons or Entity Responsible for Plan Compliance; Construction Period Pollution Prevention Measures; Erosion and Sedimentation Control Plan Drawings; Detail drawings and specifications for erosion control BMPs, including sizing calculations; Vegetation Planning; Site Development Plan; Construction Sequencing Plan; Sequencing of Erosion and Sedimentation Controls; Operation and Maintenance of Erosion and Sedimentation Controls; Inspection Schedule; Maintenance Schedule; Inspection and Maintenance Log Form.
Ш	A Construction Period Pollution Prevention and Erosion and Sedimentation Control Plan containing the information set forth above has been included in the Stormwater Report.



Cł	necklist (continued)
	andard 8: Construction Period Pollution Prevention and Erosion and Sedimentation Control ntinued)
	The project is highly complex and information is included in the Stormwater Report that explains why it is not possible to submit the Construction Period Pollution Prevention and Erosion and Sedimentation Control Plan with the application. A Construction Period Pollution Prevention and Erosion and Sedimentation Control has <i>not</i> been included in the Stormwater Report but will be submitted <i>before</i> land disturbance begins.
\boxtimes	The project is <i>not</i> covered by a NPDES Construction General Permit.
	The project is covered by a NPDES Construction General Permit and a copy of the SWPPP is in the Stormwater Report.
Ш	The project is covered by a NPDES Construction General Permit but no SWPPP been submitted. The SWPPP will be submitted BEFORE land disturbance begins.
Sta	ındard 9: Operation and Maintenance Plan
\boxtimes	The Post Construction Operation and Maintenance Plan is included in the Stormwater Report and includes the following information:
	Name of the stormwater management system owners;
	☑ Party responsible for operation and maintenance;
	Schedule for implementation of routine and non-routine maintenance tasks;
	☐ Plan showing the location of all stormwater BMPs maintenance access areas;
	Description and delineation of public safety features;
	Estimated operation and maintenance budget; and
	Operation and Maintenance Log Form.
	The responsible party is not the owner of the parcel where the BMP is located and the Stormwater Report includes the following submissions:
	A copy of the legal instrument (deed, homeowner's association, utility trust or other legal entity) that establishes the terms of and legal responsibility for the operation and maintenance of the project site stormwater BMPs;
	A plan and easement deed that allows site access for the legal entity to operate and maintain BMP functions.
Sta	andard 10: Prohibition of Illicit Discharges
	The Long-Term Pollution Prevention Plan includes measures to prevent illicit discharges;
	An Illicit Discharge Compliance Statement is attached;
	NO Illicit Discharge Compliance Statement is attached but will be submitted <i>prior to</i> the discharge of any stormwater to post-construction BMPs.



TOWN OF WESTWOOD

BOARD OF ASSESSORS

580 High St. Westwood, Ma. 02090

Maureen Bleday Michael P. Krone Mark F. Murphy

phone: 781-326-1904 fax: 781-251-2588

April 18, 2017

Anthony F & Joanne C TRS
Delapa Realty Trust
511 Washington St.
Norwood, Ma 02026

Dear Anthony & Joanne,

Attached please find a list of abutters and abutters to abutters within 300' of the locus, 16 Delapa Cir, Westwood known as Assessor's Map 29, Lot 157.

This list reflects owners of record as of January 1, 2017 or current owners, according to our records.

Mchael Wroma

Assessor



TOWN OF WESTWOOD

BOARD OF ASSESSORS

580 High St. Westwood, Ma. 02090

Maureen Bleday Michael P. Krone Mark F. Murphy

phone: 781-326-1904 fax: 781-251-2588

April 18, 2017

Anthony F & Joanne C TRS
Delapa Realty Trust
511 Washington St.
Norwood, Ma 02026

Dear Anthony & Joanne,

Attached please find a list of abutters and abutters to abutters within 300' of the locus, 16 Delapa Cir, Westwood known as Assessor's Map 29, Lot 157.

This list reflects owners of record as of January 1, 2017 or current owners, according to our records.

[[1]

Assessor



TOWN OF WESTWOOD

BOARD OF ASSESSORS

580 High St. Westwood, Ma. 02090

Maureen Bleday Michael P. Krone Mark F. Murphy

phone: 781-326-1904 fax: 781-251-2588

April 18, 2017

Anthony F & Joanne C TRS
Delapa Realty Trust
511 Washington St.
Norwood, Ma 02026

Dear Anthony & Joanne,

Attached please find a list of abutters and abutters to abutters within 300' of the locus, 16 Delapa Cir, Westwood known as Assessor's Map 29, Lot 157.

This list reflects owners of record as of January 1, 2017 or current owners, according to our records.

Michael Krone

Assessor

ABUTTERS FOR 16 DELAPA CIRCLE



MAP 29, LOT 157
WESTWOOD BOARD OF ASSESSORS




ABUTTERS FOR 16 DELAPA CIRCLE



MAP 29, LOT 157
WESTWOOD BOARD OF ASSESSORS



ABUTTERS FOR 16 DELAPA CIRCLE



MAP 29, LOT 157
WESTWOOD BOARD OF ASSESSORS



ABUTTERS LIST FOR 16 DELAPA CIRCLE WESTWOOD, MA

		Location
	i	St Zip MA 02090
		WESTWOOD
AM , GOOM TOWN	Mailing Address	580 HIGH ST 50 COACH LANE 50 COACH LANE 400 BLUE HILL DRIVE C/O DIANE GOLCHIN P O BOX 396 145 DELA PARK RD 134 DELA PARK RD 17 DELAPA CIR 31 DELAPA CIR 41 DELAPA CIR 42 DELAPA CIR 56 DELAPA CIR 72 DELAPA CIR 511 WASHINGTON ST 72 DELA PARK RD 51 WASHINGTON ST 71 DELA PARK RD 52 DELA PARK RD 53 DELA PARK RD 54 DELA PARK RD 56 DELA PARK RD 57 DELA PARK RD 58 DELA PARK RD 58 DELA PARK RD 59 DELA PARK RD 50 DELA PARK RD 51 DELA PARK RD 51 DELA PARK RD 52 DELA PARK RD 53 DELA PARK RD
	CO-OWNER	CONTE PELLEGRINO TRUSTEE PELCON REALTY TRUST KATHLEEN M CAPPUCCINO TRU CAPPUCCINO 2009 REALTY TRY C/S WESTVIEW LLC MUNZERT G CLIFFORD ETAL TRS THE ALLIED INVEST W LAND LLC HOTRA JASON M DIVINCENZO AMY S NGUYEN PHO Q D BROOKS LAURIE H COX DANIEL J DELAPA CIRCLE REATLY TRUST HOAMEI SHANG DELAPA REALTY TRUST HOAMEI SHANG BELAPA REALTY TRUST BELAPA ANTHONY F & JOANNE DELAPA REALTY TRUST SPIEGEL CHARLES T SPIEGEL SALLY SPIEGEL SALLY SPIEGEL SALLY SUZANNE DELAPA REALTY TRUST SUZANNE BELAPA REALTY TRUST SUZANNE KEVIN DELAPA REALTY TRUST SUZANNE KREINSEN HARRETT LOUISE OWN OF WESTWOOD WHARRETT LOUISE WHERE RICHARD H LAURI S T/F LAURI S T/F TRUST TRUST TRUST BANYER RICHARD H LAURI S T/F TRUST TRUST TRUST BANYER RICHARD H LAURI S T/F TRUST TRUST TRUST TRUST BANYER RICHARD H LAURI S T/F TRUST T
	OWNER	TOWN OF WESTWOOD CONSERVATION COMMISSION CONTE PELLEGRINO TRUSTE RATHLEEN M CAPPUCCINO TRU CAPPUCCINO 2009 REALTY C/S WESTVIEW LLC MUNZERT G CLIFFORD ETAL TRS THE ALLIED INVEST NW LAND LLC HOTRA JASON M DIVINCENZO AMY S NGUYEN PHO Q D BROOKS LAURIE H COX DANIEL J OLDITH L. COX HUAMEI SHANG DELAPA ANTHONY F & JOANNE DELAPA REALTY TRUST TOWN OF WESTWOOD SPIEGEL CHARLES T LUONGO MICHAEL DELAPA ANTHONY F & JOANNE DELAPA REALTY TRUST SUZANNE KREINST LEARY KEVIN GAFFIN JONATHAN M THARRETT LOUISE SAWYER RICHARD H DANIA GAFFIN TOWN OF WESTWOOD SAWYER RICHARD H DANIA GAFFIN THARRETT LOUISE RICHARD R LAURI S T/E CAPPUCCINO CAROLYN F
	LOT	2908/ 29088 29104 29114 29115 29122 29122 29150 29151 29154 29154 29155 29155 29156 29160 29161 29166 29166 29166 29169 29166 29169 29169 29169 29169

ABUTTERS LIST FOR 16 DELAPA CIRCLE WESTWOOD, MA

CO-OWNER CONSERVATION COMMISSION 580 HIGH ST PELCON REALTY TRUST 50 COACH LANE
Y TR
C/0
C/O CRESINGI HILL KEALTY P O BOX 396 KELLY N HONOHAN 145 PETA PARA PARA
134
DELA PARK
33 DELPA CIR
DELAKA CIKCLE REATLY TRUS MARYANN ARCHAMBO TRUSTEE 42 DELAPA CIR VOLPE MICHAEL 1.
DELADA REALTY TRICT
72 DRIA DADE DE
לא אמאם אנפטר ?! הם שמהם הופת 5?
DELAPA REALTY TRUST 511 WASHINGTON 5TH
511 WASHINGTON
717
7 7
81 DELA PARK
משך אט
HIGH
III DELA PARK RD
O WINTER ST

ABUTTERS LIST FOR 16 DELAPA CIRCLE WESTWOOD, MA

	Location
	NA 02090 MA 02090
	WESTWOOD
Mailing Address	TR 580 HIGH ST 50 COACH LANE 50 COACH LANE TR 146 CLAPBOARDTREE STREET 400 BLUE HILL DRIVE C/O DIANE GOLCHIN C/O DIANE GOLCHIN TR P O BOX 396 145 DELA PARK RD 17 DELAPA CIR 33 DELAPA CIR 33 DELAPA CIR 6 42 DELAPA CIR 541 DELAPA CIR 550 HIGH ST 72 DELA PARK RD 52 DELAPA CIR 541 WASHINGTON ST 73 DELA PARK RD 51 WASHINGTON ST 71 DELA PARK RD 69 DELA PARK RD 71 DELA PARK RD 71 DELA PARK RD 71 DELA PARK RD 72 DELA PARK RD 73 DELA PARK RD 74 DELA PARK RD 75 DELA PARK RD 75 DELA PARK RD 76 DELA PARK RD 77 DELA PARK RD 78 DELA PARK RD 78 DELA PARK RD 70 WINTER ST
CO-OWNER	MISSION UST NVEST L REALTY TRUSTE IST IST IST IST IST
OWNER	TOWN OF WESTWOOD CONTE PELLEGRINO TRUSTEE KATHLEEN M CAPPUCCINO TRU CAPPUCCINO 2009 C/S WESTVIEW LLC MUNZERT G CLIFFORD ETAL TOTAL JASON M DIVINCENZO AMY S NGUYEN PHO Q D BROOKS LAURIE H COX DANIEL J OLAO MING DELAPA ANTHONY F & JOANNE DELAPA REALTY TRU TOWN OF WESTWOOD SPIEGEL CHARLES T LUONGO MICHAEL DELAPA ANTHONY F & JOANNE DELAPA REALTY TRU THARRETT LOUISE TOWN OF WESTWOOD SAWYER RICHARD H LANDEL SAWYER RICHARD R LANDEL SAWYER R LANDEL SAWYER R LANDEL SAWYER R LANDEL S
MAP & LOT	29088 29104 29114 29115 29115 29122 29153 29153 29153 29154 29155 29156 29160 29161 29166 29167 29169 29169

NOTICE TO ABUTTERS Under the Massachusetts Wetlands Protection Act and Article 18, Westwood Wetland By-law

The Westwood Conservation Commission will hold a public hearing, under M.G.L.,

Notice of Intent

Chapte	r 131, Section 40 and	Article 18 of the Town of	Westwood General Bylaws on
Date:	May 24,	2017	
Time:	7:00 pm	1	
Place:	50 Carby Street,	Westwood, MA	
	Champagne Meeting	Room	
A pem	nit is requested by	DELA CONSTRUCTION (name of applicant)	CTION CO. TAK.
		511 WASHINGTON (address of applicant)	ST. Noewood, MA.
The pr	roject is located at	16 DELAPA CIA (Location of project)	ecte, NESTNOCD, MA

A complete copy of this filing is available to the public at the Office of the Town Cierk. Notice of the Conservation Commission meeting is posted in the Town Hall not less than 48 hours in advance as required by Open Meeting Law.

Westwood Conservation Commission



April 28, 2017

To whom it may concern,

Please be aware that on April 27, 2017, on behalf of Dela Construction Co. Inc., I filed a Land Disturbance Permit Application with the Westwood Conservation Commission for the proposal to develop the property located at 16 Delapa Circle in Westwood, Massachusetts. The applicant is proposing to construct a single family dwelling at 16 Delapa Circle (Lot 6) in Westwood, Massachusetts. The existing site is a 40,211 square foot undeveloped lot located off Delapa Circle at the intersection of Dela Park Road.

The application and related plans are available for examination at the Westwood Conservation Commission office, 50 Carby Street during regular office hours (phone number 781-251-2580) or at GLM Engineering Consultants, Inc by appointment (508-429-1100).

It is the abutter's responsibility to contact the Conservation Office to find out the dates and times of any subsequent hearings related to the above project.

Yours truly,

Project Manager



Exist



Proposed







Link

Routing Diagram for 9013 Lot 6
Prepared by Microsoft, Printed 4/26/2017
HydroCAD® 10.00-18 s/n 07559 © 2016 HydroCAD Software Solutions LLC

9013 Lot 6
Prepared by Microsoft
HydroCAD® 10.00-18 s/n 07559 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 2 Year Rainfall=3.20" Printed 4/26/2017

Summary for Subcatchment D-1: Proposed

Runoff

1.27 cfs @ 12.12 hrs, Volume=


0.099 af, Depth= 1.40"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-36.00 hrs, dt= 0.03 hrs Type III 24-hr 2 Year Rainfall=3.20"

_	Α	rea (sf)	CN	Description					
		15,693	79	Woods, Fai	ir, HSG D				
		1,787	98	Paved park	ing, HSG D				
		19,500	80	>75% Ġras	s cover, Go	od, HSG D		A-00	
	36,980 80 Weighted Average								
35,193 95.17% Pervious Area									
		1,787		4.83% Imp	ervious Area	a III			
	Tc	Length	Slope	Velocity	Capacity	Description			
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)		4 ×		
	7.1	50	0.0800	0.12		Sheet Flow, A-B			
						Woods: Light underbrush n= 0.400	P2= 3.20"		
	0.4	105	0.0700	4.26		Shallow Concentrated Flow, B-C			
						Unpaved Kv= 16.1 fps			
	0.7	125	0.0300	2.79		Shallow Concentrated Flow, B-C			
						Unpaved Kv= 16.1 fps			
	8.2	280	Total					·	

Page 3

Subcatchment D-1: Proposed



9013 Lot 6 Prepared by Microsoft Type III 24-hr 2 Year Rainfall=3.20" Printed 4/26/2017 Page 4

HydroCAD® 10.00-18 s/n 07559 © 2016 HydroCAD Software Solutions LLC

Runoff = 0.98 cfs @ 12.13 hrs, Volume=


Summary for Subcatchment E-1: Exist

me= 0.080 af, Depth= 1.04"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-36.00 hrs, dt= 0.03 hrs Type III 24-hr 2 Year Rainfall=3.20"

	Area (sf)	CN	Description		
	29,350	79	Woods, Fai	r, HSG D	
	10,861	60	Woods, Fai	r, HSG B	
	40,211	74	Weighted A	verage	
	40,211		100.00% Pe	ervious Area	a
To (min)		Slop (ft/ft		Capacity (cfs)	Description
7.1	50	0.080	0.12		Sheet Flow, A-B
0.4	1 105	0.070	0 4.26		Woods: Light underbrush n= 0.400 P2= 3.20" Shallow Concentrated Flow, B-C Unpaved Ky= 16.1 fps
0.7	7 125	0.030	0 2.79		Shallow Concentrated Flow, B-C Unpaved Kv= 16.1 fps
8.2	2 280	Total			

Subcatchment E-1: Exist



9013 Lot 6
Prepared by Microsoft
HydroCAD® 10.00-18 s/n 07559 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 10 Year Rainfall=4.80" Printed 4/26/2017 Page 6

Summary for Subcatchment D-1: Proposed

Runoff


2.50 cfs @ 12.12 hrs, Volume=

0.192 af, Depth= 2.72"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-36.00 hrs, dt= 0.03 hrs Type III 24-hr 10 Year Rainfall=4.80"

A	rea (sf)	CN	Description					11 9		
	15,693	79	Woods, Fa	ir, HSG D						
	1,787	98	Paved park	ing, HSG D						
	19,500	80	>75% Gras	s cover, Go	ood, HSG D					
	36,980	80	Weighted A	verage			4			
	35,193		95.17% Pe							
	1,787		4.83% Impo	ervious Are	a					
	•									
Tc	Length	Slope	e Velocity	Capacity	Description					
(min)	(feet)	(ft/ft) (ft/sec)	(cfs)		11_				
7.1	50	0.080	0.12		Sheet Flow, A-B					
					Woods: Light underbrush n= 0.400 P2= 3	3.20"				
0.4	105	0.070	4.26		Shallow Concentrated Flow, B-C					
					Unpaved Kv= 16.1 fps					
0.7	125	0.030	2.79		Shallow Concentrated Flow, B-C					
					Unpaved Kv= 16.1 fps					
8.2	280	Total								

Subcatchment D-1: Proposed



9013 Lot 6
Prepared by Microsoft
HydroCAD® 10.00-18 s/n 07559 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 10 Year Rainfall=4.80" Printed 4/26/2017 Page 8

Summary for Subcatchment E-1: Exist

Runoff = 2.19 cfs @ 12.12 hrs, Volume=

Area (sf) CN Description


0.170 af, Depth= 2.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-36.00 hrs, dt= 0.03 hrs Type III 24-hr 10 Year Rainfall=4.80"

	29,350	79	Woods, Fai	r, HSG D	
	10,861	60	Woods, Fai	r, HSG B	
	40,211 40,211		Weighted A		a
Tc (min)	Length (feet)	Slope (ft/ft)		Capacity (cfs)	Description
7.1	50	0.0800	0.12		Sheet Flow, A-B Woods: Light underbrush n= 0.400 P2= 3.20"
0.4	105	0.0700	4.26		Shallow Concentrated Flow, B-C Unpaved Ky= 16.1 fps
0.7	125	0.0300	2.79		Shallow Concentrated Flow, B-C Unpaved Ky= 16.1 fps
8.2	280	Total			

Page

Subcatchment E-1: Exist



9013 Lot 6
Prepared by Microsoft
HydroCAD® 10.00-18 s/n 07559 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 25 Year Rainfall=5.50" Printed 4/26/2017 Page 10

Summary for Subcatchment D-1: Proposed


Runoff = 3.06 cfs @ 12.12 hrs, Volume=

0.236 af, Depth= 3.33"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-36.00 hrs, dt= 0.03 hrs Type III 24-hr 25 Year Rainfall=5.50"

	Area (sf)	CN_	Description				
	15,693 1,787		Woods, Fa	ir, HSG D ing, HSG D			
	19,500				od, HSG D		
	36,980 35,193		Weighted A	lverage rvious Area			
	1,787			ervious Area			
Т	c Length	Slope	Velocity	Capacity	Description		
(mir		(ft/ft)		(cfs)	Description		
7.	1 50	0.0800	0.12		Sheet Flow, A-B	DO 0.00	
0.	4 105	0.0700	4.26		Woods: Light underbrush n= 0.400 Shallow Concentrated Flow, B-C	P2= 3.20"	
	7 405	0.0000	0.70		Unpaved Kv= 16.1 fps		
0.	7 125	0.0300	2.79		Shallow Concentrated Flow, B-C Unpaved Kv= 16.1 fps		
8.	2 280	Total					

Subcatchment D-1: Proposed



HydroCAD® 10.00-18 s/n 07559 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 25 Year Rainfall=5.50" Printed 4/26/2017 Page 12

Summary for Subcatchment E-1: Exist

Runoff

9013 Lot 6 Prepared by Microsoft


2.76 cfs @ 12.12 hrs, Volume=

0.213 af, Depth= 2.77"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-36.00 hrs, dt= 0.03 hrs Type III 24-hr 25 Year Rainfall=5.50"

Α	rea (sf)	CN	Description		
	29,350		Woods, Fai		
	10,861	60	Woods, Fai	r, HSG B	
	40,211	74	Weighted A		
	40,211		100.00% P	ervious Are	a control of the cont
Tc (min)	Length (feet)	Slop (ft/ft		Capacity (cfs)	Description
7.1	50	0.080	0.12		Sheet Flow, A-B
0.4	105	0.070	0 4.26		Woods: Light underbrush n= 0.400 P2= 3.20" Shallow Concentrated Flow, B-C Unpaved Kv= 16.1 fps
0.7	125	0.030	0 2.79		Shallow Concentrated Flow, B-C Unpaved Kv= 16.1 fps
8.2	280	Total			

Subcatchment E-1: Exist



9013 Lot 6
Prepared by Microsoft
HydroCAD® 10.00-18 s/n 07559 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 100 Year Rainfall=7.00" Printed 4/26/2017 Page 14

Summary for Subcatchment D-1: Proposed


Runoff = 4.27 cfs @ 12.12 hrs, Volume=

0.332 af, Depth= 4.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-36.00 hrs, dt= 0.03 hrs Type III 24-hr 100 Year Rainfall=7.00"

	/	Area (sf)	CN	Description						
_		15,693	79	Woods, Fai	r, HSG D					
		1,787	98	Paved park	ing, HSG D					
		19,500	80	>75% Gras	s cover, Go	od, HSG D		THE VEHICLE A	i i	1
_		36,980	80	Weighted A	verage					
		35,193		95.17% Pe	rvious Area					
		1,787		4.83% Impe	ervious Area	a				
	Tc	Length	Slope	e Velocity	Capacity	Description				
_	(min)	(feet)	(ft/ft) (ft/sec)	(cfs)					
	7.1	50	0.080	0.12		Sheet Flow, A-B				
						Woods: Light underbrush n= 0.400	P2= 3.20"			
	0.4	105	0.070	4.26		Shallow Concentrated Flow, B-C				
						Unpaved Kv= 16.1 fps				
	0.7	125	0.030	2.79		Shallow Concentrated Flow, B-C				
						Unpaved Kv= 16.1 fps				
	8.2	280	Total			· · · · · · · · · · · · · · · · · · ·				

Subcatchment D-1: Proposed



9013 Lot 6
Prepared by Microsoft
HydroCAD® 10.00-18 s/n 07559 © 2016 HydroCAD Software Solutions LLC

Type III 24-hr 100 Year Rainfall=7.00" Printed 4/26/2017 Page 16

Summary for Subcatchment E-1: Exist

Runoff = 4.04 cfs @ 12.12 hrs, Volume=

0.311 af, Depth= 4.04"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-36.00 hrs, dt= 0.03 hrs Type III 24-hr 100 Year Rainfall=7.00"

Α	rea (sf)	CN	Description		
	29,350	79	Woods, Fai	r, HSG D	
	10,861	60	Woods, Fai	r, HSG B	
	40,211	74	Weighted A	verage	
	40,211		100.00% Pe	ervious Are	B
Tc	Length	Slope			Description
(min)	(feet)	(ft/ft	(ft/sec)	(cfs)	
7.1	50	0.0800	0.12		Sheet Flow, A-B
					Woods: Light underbrush n= 0.400 P2= 3.20"
0.4	105	0.0700	4.26		Shallow Concentrated Flow, B-C
					Unpaved Kv= 16.1 fps
0.7	125	0.0300	2.79		Shallow Concentrated Flow, B-C
					Unpaved Kv= 16.1 fps
8.2	280	Total			

	
	•
••	
·	
	a de la companya de
· · · · · · · · · · · · · · · · · · ·	
) = ¹	*
	į
•	
. **	
A+	